



## Model 4330 – 5kW DC Enclosed Genset, Skid-Mounted

*Designed to Operate in Extreme Conditions*

### **General Specifications**

**Engine:** Farymann Diesel, 43F, air-cooled, 24V electric start

**Alternator:** CEN alternator, N1379-1

**Power output:** (4,000 ft/95F)

**5kW of DC**

**DC:** 28VDC current limited-178amps-regulator-NATO receptacle

Voltage regulation: < 5%

**Operating Temperature range:** -25°F (-31°C) ~ 125°F (51.7°C)

**Fuels:** Diesel DF-1, DF-2 and jet fuel JP-8

**Fuel consumption:** .95gph (3.6lph) @ rated load

**Fuel capacity/run time:** 9.5gallons/10hrs @ rated load

**Sound:** <70dBA @ 23' (7meters)

**Dimensions:** 60"X37.25"X23.5" (152X95X60cm)

**Weight-dry:** 823lbs (373kg)

### **Features**

Electric (via set mounted batteries) and/or hand-start capable, local and remote panels-customized for application, digital DC amp/volt meters, hourmeter, meets U.S. Army (PM-MEP) generator testing requirements

### **Integration/Application**

Military vehicles/mobile flight-line support

Goodman Ball, Inc. | 1-877-GBI-4PWR | [www.goodmanball.com](http://www.goodmanball.com)

